ALL ENVIRONMENT L A C s ama



Building on a legacy of continuous improvement, the Puma[™] 3AE offers system level enhancements for use in land and maritime operations. The Puma 3AE has operational flexibility never before available in the small unmanned aircraft systems (SUAS) class including upgrades for secondary payloads and third-party applications. The multi-mission capable system allows operators to swap between Mantis[™] i45 and the enhanced Mantis i45 N nighttime payload for day, night and low-light operations in extreme environments. Operators can also manually or autonomously navigate the Puma 3AE while gaining real-time situational awareness and actionable intelligence through AV's Tomahawk GCS. Available Puma[™] VTOL Kit and Puma[™] VNS (Visual Navigation System) expand the operational capabilities by providing vertical take-off and landing in urban environments and GPS-denied navigation in contested environments.

Puma[™] All-Environment Family

_Distinctions



LINK RANGE WEIGHT 12.4 mi (20 km) 15.6 lb standard, 24.8 (7.1 kg) mi (40 km) with ERA) 37.3 mi (60 km) with LRTA

 \bigcirc



ENDURANCE

2.5 hr with

Batterv¹

3 hr with

PS2500

Battery¹

TOTAL PAYLOAD CAPACITY 4 lb (1.8 kg), Puma[™] Smart 6.5 lb (2.9 kg) with Heavy Lift Software

_Specifications

PAYLOADS	Mantis™ i45: Dual 15 MP EO/IR Mantis™ i45 N: Dual LWIR/5 MP Low Light
SPEED	Cruise: 49 km/hr (26 kts) Dash: 76 km/h (41 kts)
OPERATING ALTITUDE	300–3000 ft (91–914 m) AGL, typical Max. Iaunch 10K ft (3,048 m) MSL Max Flight Altitude 10.5K ft (3,200 m) MSL
WINGSPAN	9.2 ft (2.8 m)
LENGTH	4.6 ft (1.4 m)
GCS	Tomahawk, Crysalis™, or Legacy GCS
LAUNCH METHOD	Hand-launched, optional bungee launch or VTOL kit
RECOVERY METHOD	Autonomous or manual precision deep-stall landing or VTOL kit

1. with Mantis[™] i45



DOWNLINK IMAGERY FROM MANTIS™ i45



DOWNLINK IMAGERY FROM MANTIS™ i45 N

[PLUG AND PLAY INTEROPERABLE COMPONENTS]

Puma[™] AE users can leverage existing line-replaceable units (LRUs) to easily upgrade or repair fielded systems. This interoperability builds on a legacy of Puma baselines with hundreds of thousands of operational flight hours. The Puma AE product line provides the warfighter with intelligence, surveillance and reconnaissance (ISR) during day and night operations in all-environment conditions.



[OPTIONAL ADD-ONS]



PUMA™ VTOL KIT





LAUNCH SYSTEM

PUMA[™] UNIVERSAL TRANSIT BAY



PUMA™ VNS (VISUAL NAVIGATION SYSTEM)



PUMA[™] 3 COMMS REL AY

_Key Features

- > All-environment rated, including landing in water
- > Enhanced Digital Data Link[™] covering more frequencies & supporting AES-256-bit encryption
- > Reinforced fuselage & center wing accommodates heavier configurations
- > Reduced packaging fits a flyable configuration in a single case
- > Upgraded motor providing up to 26% increased climb rate in heavier configurations for overall mission performance
- > Field-swappable Mantis[™] payloads for day & night operations

AV - ph: 703.418.2828 - www.avinc.com // @ 2025 AeroVironment, its product names and the AV logo are protected trademarks of AeroVironment, Inc. All other company, product names, logos, and brands are property of their respective owners and are for identification purposes only. Use of these names, logos, and brands does not imply endorsement. Screen images may be simulated. All specifications are subject to change. This data sheet consists of AeroVironment, Inc. general capabilities information that does not contain controlled technical data as defined within the International Traffic in Arms Regulations (ITAR) Part 120.10 or Export Administration Regulations (EAR) Part 734.7-11.

